

PRODUCT DATA SHEET

SikaProof® Patch-200 B

Self-adhesive tape for external sealing of the SikaProof® waterproofing system

DESCRIPTION

SikaProof® Patch-200 B is a single-sided, self-adhesive tape based on SikaProof® membrane, laminated with a butyl adhesive covered with a release liner.

USES

SikaProof® Patch-200 B may only be used by experienced professionals.

- Sealing and bonding overlap joints, connections and details within the SikaProof® waterproofing system

FEATURES

- Good watertightness
- Weather resistant with temporary UV-stability
- Good adhesion and durability of the Butyl-adhesive
- Self adhesion allows easy and fast installation

PRODUCT INFORMATION

Packaging	1 roll packed in a box
Appearance and colour	White release liner over black adhesive on a light yellow membrane.
Shelf life	24 months from date of production
Storage conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.
Length	20 m
Width	200 mm
Thickness	2.20 (+0.22 / -0.11) mm

APPLICATION INFORMATION

Ambient air temperature	Minimum	+5 °C
	Maximum	+45 °C
Substrate temperature	Minimum	+5 °C
	Maximum	+60 °C

SYSTEM INFORMATION

System structure

SikaProof® Patch-200 B is a system accessory for jointing and sealing details within the SikaProof® waterproofing system. For more detailed information, refer to Sika Method Statement: SikaProof® A / SikaProof® A+.

Compatibility

For materials in direct contact (such as any synthetics) the compatibility must be evaluated before full project application.
Contact Sika Technical Services for additional information.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTATION

- Sika Method Statement: SikaProof® A / SikaProof® A+
- Sika Application Manual: SikaProof® A / SikaProof® A+

IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Refer to the Sika Method Statement: SikaProof® A / SikaProof® A+
- Refer to the Product Data Sheet: SikaProof® A / SikaProof® A+

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions, which must always be adjusted to the actual site conditions.

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

SUBSTRATE QUALITY

The contact surfaces must be dry, clean and free of materials that could impair the adhesion. Contaminants, such as dirt, dust, oil, bitumen and de-bonding agents, such as surfactants and silicones must be removed.

APPLICATION

SikaProof® Patch-200 B is a cold-applied and post-applied self-adhesive tape to seal joints, connections, penetrations. Additionally, it repairs any damage to the external side of the SikaProof® system membrane. Reference must be made to the Sika Method Statement: SikaProof® A / SikaProof® A+.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE

15, Protomagias Str.
GR 145 68, Kryoneri, Attica
Tel.: +30 210 81 60 600
E-mail: info@gr.sika.com
www.sika.gr



Product Data Sheet
SikaProof® Patch-200 B
August 2025, Version 04.01
020720308000000005

SikaProofPatch-200B-en-GR-(08-2025)-4-1.pdf