

SikaMur[®] Finish

DECLARATION OF PERFORMANCE

No. 90119459

1	UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE:	90119459
2	INTENDED USE/S	EN 998-1:2010 General purpose rendering/plastering mortar (GP) for in- and external use
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8048 Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 998-1:2010

Declaration of Performance

SikaMur[®]-Finish

90119459

2017.08, Revision 2

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Compressive strength	CS I	EN 998-1:2010
Adhesion	> 0,2 N/mm ² - FP:B	
Capillary water absorption	W0	
Water vapour permeability coefficient	$\mu \leq 15$	
Thermal conductivity ($\lambda_{10, dry}$)	0,27 W/mK	
Reaction to fire	Euroclass A1	
Dangerous substances	NPD	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 12 May 2020

Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 12 May 2020



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaMur®-Finish
90119459
2017.08, Revision 2





15

Sika Services AG, Zürich, Switzerland

DoP 90119459

Notified body 1026

EN 998-1:2010

General purpose rendering/plastering mortar (GP) for in- and external use

Compressive strength	CS I
Adhesion	> 0,2 N/mm ² - FP: B
Capillary water absorption	W0
Water vapour permeability coefficient	$\mu \leq 15$
Thermal conductivity ($\lambda_{10, dry}$)	0,27 W/mK
Reaction to fire	Euroclass A1

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaMur®-Finish
90119459
2017.08, Revision 2



Sika Hellas ABEE
Protomagias 15
14568, Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
SikaMur®-Finish
90119459
2017.08, Revision 2