

EN 13813



DECLARATION OF PERFORMANCE

ACCORDING ANNEX III OF THE REGULATION (EU) NO 305/2011

Sikafloor[®]-400 Level No. 115041503

1	UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE:	115041503
2	INTENDED USE/ES	EN 13813 Cementitious levelling compound
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4 / System 3 for reaction to fire
6a	HARMONIZED STANDARD:	EN 13813
	Notified body/ies:	1378

Declaration of PerformanceSikafloor[®]-400 Level
115041503
2015.04 , Revision 1.0

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire class	A2 _{fl} - s1	EN 13813
Release of corrosive substances	CT	
PH value	NPD	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C35	
Flexural strength	F7	
Wear resistance	NPD	
Tensile adhesion strength	NPD	
Shock resistance	NPD	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Bond strength	NPD	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis
Function: TMM Flooring
At Athens on 23 March 2020



Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 23 March 2020



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sika floor®-400 Level
115041503
2015.04 , Revision 1.0



1378

15
115041503

EN 13813

Cementitious leveling compound

Reaction to fire class	A2fl - s1
Release of corrosive substances	CT
PH value	NPD
Water permeability	NPD
Water vapour permeability	NPD
Compressive strength	C35
Flexural strength	F7
Wear resistance	NPD
Tensile adhesion strength	NPD
Shock resistance	NPD
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD
Bond strength	NPD

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika floor®-400 Level
115041503
2015.04 , Revision 1.0



Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Athens-Greece
www.sika.gr

Declaration of Performance
Sika floor®-400 Level
115041503
2015.04 , Revision 1.0