

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sikadur® Injection Resin Part B

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE  
15 Protomagias Street  
145 68 Kryoneri / Athens  
Telephone : +30 210 81 60 600  
Telefax : +30 210 81 60 606  
E-mail address of person : EHS@gr.sika.com  
responsible for the SDS

### 1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 + H312 Harmful if swallowed or in contact with skin.

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

	H314	Causes severe skin burns and eye damage.
	H317	May cause an allergic skin reaction.
	H361	Suspected of damaging fertility or the unborn child.
	H372	Causes damage to organs through prolonged or repeated exposure.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	<b>Prevention:</b>	
	P202	Do not handle until all safety precautions have been read and understood.
	P260	Do not breathe mist or vapours.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	<b>Response:</b>	
	P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
	P391	Collect spillage.
	<b>Storage:</b>	
	P405	Store locked up.
	<b>Disposal:</b>	
	P501	Dispose of contents/container in accordance with local regulation.

**Hazardous components which must be listed on the label:**

Phenol, methylstyrenated  
2-piperazin-1-ylethylamine  
Phenol, styrenated  
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine  
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine  
3-aminopropyltriethoxysilane  
3-aminopropyl dimethylamine



### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Phenol, methylstyrenated	Not Assigned 700-960-7 270-966-8 01-2119555274-38-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 40 - < 60
2-piperazin-1-ylethylamine Contains: 2-(2-aminoethylamino)ethanol <= 0,29 %	140-31-8 205-411-0 01-2119471486-30-XXXX	Acute Tox. 3; H311 Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Repr. 2; H361 STOT RE 1; H372 Eye Dam. 1; H318	>= 10 - < 20
Phenol, styrenated	61788-44-1 262-975-0 01-2119980970-27-XXXX, 01-2119979575-18-XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 10 - < 20
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 10 - < 20
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 5 - < 10

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**Sikadur® Injection Resin Part B**

Revision Date: 22.06.2022

Version 2.0

Print Date 22.06.2022

Date of last issue: 18.11.2021

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1 500-191-5 01-2119972320-44-XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 3 - < 5
salicylic acid	69-72-7 200-712-3 01-2119486984-17-XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	>= 3 - < 5
1,3-Cyclohexanedimethanamine	2579-20-6 219-941-5 01-2119543741-41-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 3 - < 5
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	186321-96-0 606-078-8 01-2119983521-35-XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 3 - < 5
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48-XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 0,25 - < 1
3-aminopropyltriethoxysilane	919-30-2 213-048-4 01-2119480479-24-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317  Acute toxicity estimate  Acute oral toxicity: 1.490 mg/kg	< 1
3-aminopropyldimethylamine	109-55-7 203-680-9 01-2119486842-27-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Acute Tox. 4; H312 STOT SE 3; H335	< 1

For explanation of abbreviations see section 16.



---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort  
Allergic reactions  
Dermatitis  
Skin disorders  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.  
corrosive effects  
sensitising effects
- Harmful if swallowed or in contact with skin.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Suspected of damaging fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure.  
Causes severe burns.



---

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.



---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

- Hand protection : Wear eye/face protection.  
: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : No special measures required.
- Environmental exposure controls**
- General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Colour : light brown  
Odour : amine-like
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Flash point : > 101 °C  
Method: closed cup
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available



SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

pH : Not applicable  
substance/mixture is non-soluble (in water)

**Viscosity**

Viscosity, dynamic : ca. 500 mPa.s (20 °C)

Viscosity, kinematic : No data available

**Solubility(ies)**

Water solubility : insoluble

Partition coefficient: n-  
octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,00 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

The product is chemically stable.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.

**10.4 Conditions to avoid**

Conditions to avoid : No data available

**10.5 Incompatible materials**

Materials to avoid : Acids  
Oxidizing agents  
Peroxides

No data available

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

**10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

---

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Harmful if swallowed or in contact with skin.

**Components:**

**2-piperazin-1-ylethylamine:**

Acute oral toxicity : LD50 Oral (Rat): > 1.999 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg

**Phenol, styrenated:**

Acute oral toxicity : LD50 Oral (Rat): 2.500 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

**2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg  
Remarks: Harmful if swallowed.  
Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

**benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

**salicylic acid:**

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

**1,3-Cyclohexanedimethanamine:**

Acute oral toxicity : LD50 Oral (Rat): 780 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rat): 1.700 mg/kg

**bis(isopropyl)naphthalene:**

Acute oral toxicity : LD50 Oral (Rat): > 3.900 mg/kg

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

Acute inhalation toxicity : LC50 (Rat): > 5,64 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4.500 mg/kg

**3-aminopropyltriethoxysilane:**

Acute oral toxicity : LD50 Oral (Rat): 1.490 mg/kg

Acute toxicity estimate: 1.490 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

**Skin corrosion/irritation**

Causes severe burns.

**Components:**

**2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Corrosive  
Method : OECD Test Guideline 404

Assessment : irritating  
Remarks : Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Components:**

**2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Causes serious eye damage.

Assessment : irritating  
Remarks : Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.



**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Components:**

**2-piperazin-1-ylethylamine:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

**2,4,6-tris(dimethylaminomethyl)phenol:**

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h

**benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

**Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Sikadur® Injection Resin Part B



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): 7,07 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 4,34 mg/l Exposure time: 72 h  NOEC (Pseudokirchneriella subcapitata (green algae)): 0,5 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC50: 7,07 mg/l Exposure time: 48 d Species: Daphnia sp. (water flea)

### **Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine:**

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0,705 mg/l Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



## 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 2735  
IMDG : UN 2735  
IATA : UN 2735

### 14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.  
(2-piperazin-1-ylethylamine)  
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.  
(2-piperazin-1-ylethylamine)  
IATA : Amines, liquid, corrosive, n.o.s.  
(2-piperazin-1-ylethylamine)

### 14.3 Transport hazard class(es)

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

**ADR** : 8  
**IMDG** : 8  
**IATA** : 8

#### 14.4 Packing group

**ADR**  
Packing group : II  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : (E)

**IMDG**  
Packing group : II  
Labels : 8  
EmS Code : F-A, S-B

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 855  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosive

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 851  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosive

#### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

**IATA (Passenger)**  
Environmentally hazardous : no

**IATA (Cargo)**  
Environmentally hazardous : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH Information:		All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

#### E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 5,4% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 5,8% w/w

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.





---

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H361	:	Suspected of damaging fertility or the unborn child.
H361d	:	Suspected of damaging the unborn child.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sikadur® Injection Resin Part B**



Revision Date: 22.06.2022  
Date of last issue: 18.11.2021

Version 2.0

Print Date 22.06.2022

MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

**Further information**

**Classification of the mixture:**

Acute Tox. 4	H302
Acute Tox. 4	H312
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 2	H361
STOT RE 1	H372
Aquatic Chronic 2	H411

**Classification procedure:**

Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GR / EN