
SikaGrout[®]-340

DECLARATION OF PERFORMANCE

No. 72169369

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	72169369
2	INTENDED USE/S	EN 1504-6:2006 Anchoring product for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works Principle 4, method 4.2 of EN 1504-9:2008
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 4
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	0099

Declaration of Performance

SikaGrout[®]-340
72169369
2018.08 , ver. 1
1053

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Pull-out strength	Displacement ≤ 0.6 mm at load of 75 kN	System 2+	EN 1504-6:2006
Chloride ion content	NPD		
Glass transition temperature	NPD		
Reaction to fire	A1	System 4	
Durability/Creep under tensile load	NPD		
Dangerous substances	NPD		


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
 Function: TMM Refurbishment
 At Athens on 23 April 2020

Name: Alexandros Melissourgos
 Function: Technical Manager
 At Athens on 23 April 2020




End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
SikaGrout®-340	EN 1504-3:2005	89923053



18

Declaration of Performance

SikaGrout®-340
 72169369
 2018.08 , ver. 1
 1053



Sika Services AG, Zurich, Switzerland	
DoP No. 72169369	
EN 1504-6:2006	
Notified Body 0099	
Anchoring product for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works, Principle 4 (method 4.2) of EN 1504-9:2008	
Pull-out strength	Displacement \leq 0.6 mm at load of 75 kN
Reaction to fire	A1
http://dop.sika.com	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaGrout®-340
72169369
2018.08 , ver. 1
1053



Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
SikaGrout®-340
72169369
2018.08 , ver. 1
1053