

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaWall®-6400 Fire Acrylic

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Acrylate coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE  
15 Protomagias Street  
145 68 Kryoneri / Athens  
Telephone : +30 210 81 60 600  
Telefax : +30 210 81 60 606  
E-mail address of person : EHS@gr.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777  
Poison Information Center: 1401 (Cyprus)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

### Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one (BIT)  
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

### Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 55965-84-9, 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5. Please use treated articles responsibly.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025

Version 8.0

Print Date 12.11.2025

Date of last issue: 30.07.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60-XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1A; H317 >= 0,036 %  Acute toxicity estimate  Acute oral toxicity: 450 mg/kg Acute inhalation toxicity (dust/mist): 0,21 mg/l	>= 0,0025 - < 0,025

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



**SikaWall®-6400 Fire Acrylic**

Revision Date: 10.11.2025

Version 8.0

Print Date 12.11.2025

Date of last issue: 30.07.2025

<p>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)</p>	<p>55965-84-9 Not Assigned 01-2120764691-48-XXXX</p>	<p>Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit Skin Corr. 1C; H314 &gt;= 0,6 %</p> <hr/> <p>specific concentration limit Skin Irrit. 2; H315 0,06 - &lt; 0,6 %</p> <hr/> <p>specific concentration limit Eye Irrit. 2; H319 0,06 - &lt; 0,6 %</p> <hr/> <p>specific concentration limit Skin Sens. 1A; H317 &gt;= 0,0015 %</p> <hr/> <p>specific concentration limit Eye Dam. 1; H318 &gt;= 0,6 %</p>	<p>&gt;= 0,0015 - &lt; 0,0025</p>
--	--	---	-----------------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025

Version 8.0

Print Date 12.11.2025

Date of last issue: 30.07.2025

Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17-XXXX		>= 1 - < 2,5

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : sensitising effects  
  
May cause an allergic skin reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA (inhalable)	10 mg/m <sup>3</sup>	GR OEL
		TWA (respirable)	5 mg/m <sup>3</sup>	GR OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

Viton gloves (0.4 mm),  
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Form : paste  
Colour : various  
Odour : characteristic
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Flash point : Not applicable
- Auto-ignition temperature : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

Decomposition temperature : No data available  
pH : ca. 9 (20 °C)  
Concentration: 100 %

### Viscosity

Viscosity, dynamic : ca. 18.500 mPa.s (20 °C)  
Viscosity, kinematic : No data available

### Solubility(ies)

Water solubility : partly miscible  
Partition coefficient: n-octanol/water : No data available  
Vapour pressure : Not applicable  
Density : ca. 1,86 kg/l (20 °C)  
Relative vapour density : No data available  
Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Components:

##### **1,2-benzisothiazol-3(2H)-one (BIT):**

Acute oral toxicity : Acute toxicity estimate: 450 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LD50 Oral (Rat): 450 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 0,21 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LC50: 0,21 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

##### **Skin corrosion/irritation**

Not classified due to lack of data.

##### **Serious eye damage/eye irritation**

Not classified due to lack of data.

##### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified due to lack of data.

##### Components:

##### **1,2-benzisothiazol-3(2H)-one (BIT):**

Assessment : May cause sensitisation by skin contact.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

Not classified due to lack of data.

### **STOT - repeated exposure**

Not classified due to lack of data.

### **Aspiration toxicity**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

Not classified due to lack of data.

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

#### **1,2-benzisothiazol-3(2H)-one (BIT):**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3 mg/l  
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

#### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic toxicity) : 100

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025

Version 8.0

Print Date 12.11.2025

Date of last issue: 30.07.2025

- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 40:

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: < 0,01% w/w  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0,05% w/w

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025

Version 8.0

Print Date 12.11.2025

Date of last issue: 30.07.2025

### SECTION 16: Other information

#### Full text of H-Statements

H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H310	:	Fatal in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
GR OEL	:	Greece. Exposure limit values
GR OEL / TWA	:	Long term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaWall®-6400 Fire Acrylic



Revision Date: 10.11.2025  
Date of last issue: 30.07.2025

Version 8.0

Print Date 12.11.2025

---

### Further information

#### Classification of the mixture:

Skin Sens. 1                      H317

#### Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GR / EN