

PRODUCT DATA SHEET

SikaProof® Fix Tape-50

DOUBLE-SIDED ADHESIVE TAPE FOR THE SIKAPROOF® WATERPROOFING SYSTEM

DESCRIPTION

SikaProof® Fix Tape-50 is a double-sided, self-adhesive tape based on a butyl rubber adhesive covered with a release liner

USES

SikaProof® Fix Tape-50 may only be used by experienced professionals.

- Sealing and bonding of details within the SikaProof® Waterproofing System.

CHARACTERISTICS / ADVANTAGES

- Good adhesion and sealing capability
- Good durability
- Self adhesion allows easy and fast installation

PRODUCT INFORMATION

Packaging	5 rolls packed in one box
Appearance / Colour	White release liner over black butyl rubber adhesive.
Shelf life	24 months from date of production
Storage conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.
Length	20 m
Width	50 mm
Thickness	1,50 mm (-5/+10 %)

SYSTEMS

System Structure	SikaProof® FixTape-50 is a system accessory for sealing specific details within the SikaProof® Waterproofing System. For more detailed information, refer to the Sika Method Statement: SikaProof® A / SikaProof® A+.
Compatibility	For materials in direct contact (such as any synthetics etc.) the compatibility must be evaluated before full project application. Contact Sika Technical Services for additional information.

APPLICATION INFORMATION

Ambient Air Temperature +5 °C min. / +45 °C max.

Substrate Temperature +5 °C min. / +60 °C max.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surfaces of the membrane must be dry, clean and free of materials that could impair adhesion. Contaminants, such as dirt, dust, oil, bitumen and debonding agents, such as surfactants and silicones must be removed.

APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Reference must be made to the Sika® Method Statement: SikaProof® A / SikaProof® A+.

FURTHER INFORMATION

- Sika Method Statement: SikaProof® A / SikaProof® A+
- Sika Application Manual: SikaProof® A / SikaProof® A+

IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Refer to the Sika Method Statement: SikaProof® A / SikaProof® A+
- Product Data Sheet: SikaProof® A / SikaProof® A+

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE

15 Protomagias Str.
14568 Kryoneri
Attica-Greece
Tel.: +30 210 8160 600
Fax: +30 210 8160 606
www.sika.gr | sika@gr.sika.com



Product Data Sheet

SikaProof® Fix Tape-50
December 2019, Version 02.01
020704210220000005

SikaProofFixTape-50-en-GR-(12-2019)-2-1.pdf